




Une traçabilité fiable
Reliable traceability

LiveTrack® Reader

Used globally, the LiveTrack® reader is the most advanced and affordable ISO Industrial hand held wand reader. With a memory of up to 10,000 RFID tags, it improves performance and lowers overhead while processing EID in harsh environments. Conceived with the help of industrial systems integrators and others the LiveTrack® reader is **robust and easy to use**, making it an ideal solution for Identification in Industrial applications, where a Rugged RFID Reader is needed.

Technical Data

Case:	Polycarbonate ABS
Operating Frequency:	125.0 kHz, 134.2 kHz
RFID Compatibility:	Industrial HDX, ISO FDX-B, HDX
Reading Distance:	25-35 cm, 10-14 Inches
Memory:	10, 000 tags
Communication Ports:	Serial RS232 or optional Bluetooth (Class1, 100m)
Battery Power:	7.4V Li-ion rechargeable
Power Input:	12 VDC for charging the battery
Protection Class:	IP 66
Dimensions:	65 X 10 X 3cm 26 x 4 x 1.2"
Weight:	0.7 kg or 1.5 lbs
Display:	"OLED" 126 x 64 pixels
Display Languages:	English, French, Spanish
Certifications:	IC, FCC, CE, C-Tick
Included in the box:	Quick Start Guide, Reader, LiveTrack® Manager Software CD, Manual, Hand Strap, Serial Cable and 12v DC international power supply



LiveTrack[®] Manager Software

Out of the box tracking solution

Reader's Info

ID: **LIVETRACK 180-LTL03146**
 Firmware: **VF05.16r 2008-11-05**
 Temperature: **00 Celsius**
 Battery: **7.51 Volts**
 Date: **2009-02-25**
 Time: **09:50:51** [Synchronize]

Memory

Number of Tags: **00245**
 [Download] [Erase]

Counter

Tag Counter: **00233**
 [Reset]

String Format

Tag Type Tag ID Scan Time Scan Site [Save]
FCCDDDDDDDDDDDDAASSMMHHWWDDMMYYTTTTTTT [?]

Settings

Language: French [Save]
 Site Number: 1453409 [Save]
 Allow Duplicates in Reader
 Continuous Read Vibrator
 Single Read Buzzer

Turn Off Delays
 Delays from 30 to 9999 (Sec)
 Bluetooth: [0120]
 Antenna: [0060]
 Reader: [0120]
 [Save]

Bluetooth Master/Slave

000000000000 [Current: Slave]
 [Master] [Slave]

Read Log

Type	Tag ID	Date	Time	Site #
F	124000312959256	30-12-2008	12:54:25	1453409
F	124000313257363	30-12-2008	12:54:37	1453409
F	124000312959301	30-12-2008	12:54:44	1453409
F	124000312959251	30-12-2008	12:54:56	1453409
F	124000312099628	30-12-2008	12:55:21	1453409
F	124000312959303	30-12-2008	12:55:27	1453409
F	124000312099608	30-12-2008	12:55:34	1453409
F	124000313257362	30-12-2008	12:55:42	1453409
F	124000312507694	30-12-2008	12:55:57	1453409
0	000000000000000	30-12-2008	13:16:00	1453409
F	124000313031506	30-12-2008	13:16:23	1453409
F	124000313031523	30-12-2008	13:16:35	1453409
F	124000313031512	30-12-2008	13:16:41	1453409
F	124000313031557	30-12-2008	13:16:46	1453409
F	124000313031562	30-12-2008	13:16:52	1453409
F	124000313031514	30-12-2008	13:17:00	1453409
F	124000313031564	30-12-2008	13:17:09	1453409
F	124000313031516	30-12-2008	13:17:13	1453409
F	124000313031540	30-12-2008	13:17:18	1453409
F	124000313031516	30-12-2008	13:17:27	1453409
F	124000313031527	30-12-2008	13:17:32	1453409

[Save Log] [Clear Log] **00245**
 .CSV .TXT Remove Duplicates in Log

[Reset to Default Settings]

Advantages

- ISO 11784 and 11785 compliance
- Reads Industrial Tags, FDX-B and HDX
- Light weight, ergonomic design
- Robust construction
- Read confirmation via vibration and sound
- Best graphic visibility
- Water Proof/Air tight
- Easy battery exchange
- Includes international power supply
- Languages: English, French and Spanish
- Simple PC/Laptop configuration
- Contact Syscan for other Livestock traceability solutions to fit your needs



SYSCAN-ID inc.
 1975 Hymus, suite 225
 Dorval, QC H9P 1J8 CANADA
 Tel. 1 514 685 7778
 Fax 1 514 685 1938
 www.syscan-id.com